



**HTR**

**TRYK AKKUMULATOR  
HYDROPNEUMATIC ACCUMULATOR**



1



2

Varenr. Code	Type	Tegning Drawing	Nitrogen	Q MAX l/min	P MAX bar	H	ØD	B	C	F	kg
ACHTR00350	HTR 0.35	1	lt 0.35	45	250	155	93	20	15	M18x1.5	2.50
ACHTR00700	HTR 0.7	1	lt 0.75	40	250	220	93	20	15	M18x1.5	3.70
ACHTR01500	HTR 1.5	1	lt 1.50	40	250	280	115	25	15	M18x1.5	5.30
ACHTR02500	HTR 2.5	2	lt 2.50	110	250	483	115	50	15	3/4" BSP	11.50
ACHTR04501	HTR 4.5	2	lt 4.50	400	210	395	170	80	15	1"1/4 BSP	15.00
ACHTR06500	HTR 6.5	2	lt 6.50	350	210	520	170	60	20	1"1/4 BSP	24.00
ACHTR10000	HTR 10	2	lt 10.00	300	210	760	170	80	15	1"1/4 BSP	31.00
ACHTR20000	HTR 20	2	lt 19.50	600	150	845	220	110	15	2" BSP	59.00
ACHTR35000	HTR 35	2	lt 35.00	540	150	1500	220	110	15	2" BSP	90.00
ACHTR50000	HTR 50	2	lt 50.00	500	150	1990	220	110	15	2" BSP	121.00

Temperatur C° - Temperature C° : -20°C - +80°C

MATERIALE - MATERIAL :

HUS - BODY: STÅL - STEEL      BLÆRE - BLADDER : NBR